

HD 8 CH 1080P Mobile DVR

M728 (G4F)



4G
 GPS/Glonass
 WIFI
 AI
 Car Plate license recognition
 DSM
 ADAS
 trunking intercom

Main Features

- Supports 8 CH 1080P recording resolution ,AHD/TVII/CVI / CVBS hybrid mode supported
- Supports real-time remote viewing through 4G/3G/WIFI (optional)
- Supports Hard disk for main recording,Supports SD card for mirror recording;
- supports pre-recording for alarm events, motion detection alarm, alarm linkage etc
- UPS function, the power is switch off , the DVRs still can work for 7s to protect the Recording data to be complete.
- Support two way talking and trunking intercom via 4G or WIFI
- Support to recognize the car Plate license numbers
- DSM solution , TO connect the DSM camera ,to detect driver abnormal driving status. including fatigue, distraction, smoking and making a phone while driving.
- ADAS solution ,to connect the ADAS camera ,To provide early warning in real time to reduce the driving risks.

Specification

OS	Linux	
Language	English/Chinese/Customized	
Video Compression	H.264 Compression	
Video Record System	Video Input	8CH AHD input,CVI,TVI or CVBS aviation connector, 1.0Vp-p, 75Ω
	Video output	1 CVBS, 1.0Vp-p, 75Ω,Aviation,Support 1CH Full Screen,8CH Screen view
	Resolution	8*CVI/8*HD1/8*D1. 8*720P/8*1080P(MAX 120 FPS)
	Image Quality	0-7 levels, 0 is the highest level.
audio Compression	G.726 compression, 8KB/s speed	
Alarm Input	6CH Alarm Input,1CH AD Input,impulse speed input,Alarm Linkage	
Alarm Output	2CH Alarm Output,Support Light/Sound alarm sensor,Oil/Power cut off	
Interface	2CH RS232 to connect OBD, POS/Fuel Sensor/LED Advertisement Connection,1CH 485 Interface	
4G/3G	Built in 4G module optional, TDD-LTE, FDD-LTE, WCDMA	
GPS Position	Support Built GPS/BD Module	
WIFI	2.4G HZ or 5G HZ	
Storage	Max 2.5" 4TB HDD+Max 128GB SD Card Mirror	
USB Interface	USB Interface on Front Panel for data back up by U Disk,Hard Disk	
Video playback	Max support 8CH Replay /Stop/Fast/Slow at same time	
Optional Functions	Support voice call each other	
	Support TTS voice broadcast function.	
	Support LED Advertisement Panel,Oil Sensor, ADAS ,DSM,Car OBD, two way talking ect.	
Voltage & Power	Wide Voltage.Support DC:+10V - +36V	
	output Voltage : +12V-1.5A,+5V-1.5A	
Working Environment	-20°C - +70°C	
others	218 (D)* 161(W)* 65(H) mm	
	2.2 Kg	